



Nicholl Food Packaging

dual ovenable board



key benefits of ovenable board

- Environmentally sound paper board which is recyclable* & biodegradable*
- Recycled from renewable sources up to 7 times
- Ovenable to 220 degrees C
- Microwavable
- Freezer to -40 degrees C
- Cool to touch when taken out of the oven or microwave
- Aesthetically appealing
- Customer friendly – easy to open and peel
- Polyester film lining provides a liquid leak proof barrier
- Strong board design that will not collapse during the cooking process
- Bespoke shapes and colours available

*except for tray liner



product range:

	Volume (cc)	Nicholl Product Code	Top Out (mm)	Top In (mm)	Base (mm)	Depth (mm)	Case (qty)	Pallet Quantity (UK)	Quantity (Euro)	Case Weight (kg)
	155	SC38 - 200	92	81	65	37	1000	40,000	30,000	14.1
	205	SC4 - 200	126	113	76	29	1400	56,000	42,000	12.3
	220	SC67 - 200	98	80	42	60	900	28,800	21,600	10.0
	290	SC6 - 200	120 x 120	108 x 108	78 x 78	35	1500	48,000	36,000	16.4
	330	SC27 - 200	125	104 x 106	92 x 85	45	600	19,200	14,400	9.0
	350	SC49 - 200	170 x 110	156 x 93	142 x 82	31	1000	24,000	18,000	13.0
	380	SC69 - 200	171 x 103	160 x 92	144 x 76	31	1000	24,000	18,000	12.0
	420	SC52 - 200	122 x 122	106 x 106	78 x 78	50	900	28,800	21,600	17.7
	460	SC10 - 200	164 x 127	148 x 111	123 x 86	35	840	26,880	20,160	11.8
	535	SC64 - 200	165	147	132	35	540	12,960	9,720	8.0
	540	SC62 - 200	165 x 122	151 x 109	124 x 82	47	900	21,600	16,200	14.0
	625	SC33 - 200	186 x 136	174 x 124	160 x 110	33	360	11,520	8,640	6.0
	670	SC54 - 200	200 x 115	184 x 99	156 x 71	50	480	15,360	11,520	9.4

product range:

	Volume (cc)	Nicholl Product Code	Top Out (mm)	Top In (mm)	Base (mm)	Depth (mm)	Case (qty)	Pallet Quantity (UK)	Quantity (Euro)	Case Weight (kg)
	870	SC63 - 200	176	161	137	46	465	11,160	8,370	10.0
	900	SC57 - 200	210 x 140	196 x 126	170 x 100	45	480	11,520	8,640	10.0
	900	SC58 - 200	186	172	150	45	465	11,160	8,370	10.2
	1000	SC66 - 200	292 x 260	272 x 240	252 x 222	18	320	10,240	7,680	8.4
	1070	SC61 - 200	257 x 190	240 x 175	213 x 154	30	450	14,400	10,800	13.0
	1100	SC55 - 200	225 x 196	212 x 184	191 x 163	36	300	7,200	5,400	8.1
	1250	SC60 - 200	257 x 190	240 x 175	206 x 148	38	430	13,760	10,320	13.1
	1280	SC17 - 200	250 x 162	238 x 148	212 x 122	44	375	9,000	6,750	10.2
	1450	SC51 - 200	260 x 172	248 x 160	222 x 134	44	375	9,000	6,750	11.0
	1500	SC56 - 200	228 x 196	214 x 182	185 x 153	52	250	6,000	4,500	7.5

product range: uncoated

	Volume (cc)	Nicholl Product Code	Top Out (mm)	Top In (mm)	Base (mm)	Depth (mm)	Case (qty)	Pallet Quantity (UK)	Quantity (Euro)	Case Weight (kg)
	360	FC300 - 200	190 x 138	178 x 126	150 x 100	20	1000	32,000	24,000	12.0



Nicholl Food Packaging

product capability

Using Nicholl's Dual-Ovenable Board trays and a suitable film lid, a leakproof pack is achievable for a variety of chilled and frozen applications. Recipe dishes that contain sauces, grease, oils and gravy can also be accommodated, and packs remain consistently leakproof whilst in transit, storage, refrigeration and through to consumption.

Dual-Ovenable Board trays used in conjunction with film lidding for chilled applications present numerous advantages over traditional tray materials. In microwave and conventional cooking conditions, trays remain rigid which in turn keeps the contents of the pack intact and provides safe handling of the end product to the consumer. Trays can be printed with either a registered or random design to offer an enhanced pack presentation, compared to either plain Ovenable Board trays or CPET trays.



UK

Nicholl Food Packaging Limited, Walkmill Lane, Cannock, Staffordshire WS11 0XA
Tel: +44 (0) 1543 460400 Fax: +44 (0) 1543 460600 Email: sales@nfpfoil.com www.nfpfoil.com

international offices

North America

Nicholl Food Packaging
113 McHenry Road, # 242
Buffalo Grove, IL 60089-1797
USA

Tel: 847 353 8888
Fax: 847 353 8889
Email: sales@nfpfoil.com
www.nfpfoil.com

France

Ecopla France SAS
B.P.5
F-38660 Saint-Vincent-De-Mercuze
France

Tel: +33 (0) 476 92 3230
Fax: +33 (0) 476 92 3232
Email: sales@ecopla.fr
www.ecopla.fr

Germany

Bachmann Aluminium GmbH
Hauptstraße 46
D-30952 Ronnenberg / OT Weetzen
Germany

Tel: +49 (0) 51 09 / 52 93-0
Fax: +49 (0) 51 09 / 32 98
Email: sales@bachmann-aluminium.de
www.bachmann-aluminium.de

Belgium

Ecopla Benelux sprl
Parc Industriel
B - 5300 Seilles
Belgium

Tel: +32 (0) 85 82 32 20
Fax: +32 (0) 85 82 56 02
Email: sales@ecopla.be
www.ecopla.be